

ACUAFLEX



APPLICATIONS

- Transfer of water at up to 4 bar
- Drop-wise irrigation systems
- Liquid fertilisers
- Protection sleeves

CHARACTERISTICS

Composition: Single layer lay- flat PVC hose. Polyester textile reinforcement.

Characteristics: Maximum resistance to the elements.

Service Temperature: >From 0 °C to +60 °C

Standard Length: 50 and 100 m

Identification: Smooth internal and external surface. Blue colour and marked ACUAFLEX



Code	Nominal diameter		Service/Bursting Pressure bar	Roll length m	Maximum flow rate liters / hour
	mm.	Inches			
-	30	-	4 / 14	50 y 100	6.000
01401	40	-	4 / 13	50 y 100	9.000
-	45	1 3/4	4 / 12	50 y 100	12.000
01402	51	2	4 / 12	50 y 100	16.000
01403	55	2 1/4	4 / 12	100	19.000
-	60	-	3 / 10	100	22.000
-	63	-	3 / 10	100	24.000
01404	65	2 1/2	3 / 10	50 y 100	25.000
01405	70	-	3 / 10	100	30.000
01406	75	-	3 / 10	100	37.000
01407	77	3	3 / 10	50 y 100	38.000
01408	90	3 1/2	2 / 8	100	50.000
01409	100	-	2 / 7	100	60.000
01410	102	4	2 / 6	50 y 100	62.000
01411	110	-	1,5 / 6	100	76.000