

RYLSOL MARTILLO



Applications:

Hose for construction hammers and pneumatic applications up to 20 bar working pressure.

Material:

SBR / EPDM rubber tubing reinforced with polyester fabric.

Surface:

Smooth

Identification:

Marked Rylosol Martillo. 20 bar

Colour: Black

Standard length:

100 m rolls up to 13 mm in diameter.

50 m rolls from 15 mm up to 25 mm in diameter.

Temperature Range:

-20°C to 80°C.

Packaging:

Yellow polyethylene tape.

Standard:

ISO 1307.

APPLICATION:

Rubber hose for pneumatic hammers for construction work at 20 bar pressure.

TECHNICAL DATA

Code	Internal-External Diameter (mm)	Service Pressure (bar)	Bursting Pressure (bar)	Standard Length (m)
02195	6 x 14	20	60	100
02196	8 x 16	20	60	100
02197	10 x 18	20	60	100
02198	12 x 20	20	60	100
02199	13 x 21	20	60	100
02200	15 x 25	20	60	50
02203	19 x 29	20	60	50
02202	25 x 35	20	60	50

TECHNICAL DATA

Code	Internal-External Diameter (mm)	Weight (g/m)	Roll Weight (kg)	Roll Dimensions (cm)
02195	6 x 14	190	19	40x40x20
02196	8 x 16	230	23	45x45x20
02197	10 x 18	295	29	50x50x20
02198	12 x 20	310	31	54x54x20
02199	13 x 21	320	32	56x56x20
02200	15 x 25	460	46	50x50x20
02203	19 x 29	570	57	55x55x20
02202	25 x 35	700	70	62x62x25