

## RYLSOL MULTI



### Applications:

Pneumatic tools, air distribution. (20 bar).  
Fumigation. Cleaning and air distribution.  
Non-toxic use.

### Material:

Multipurpose thermorubber inner tube with textile reinforcement of high tenacity synthetic fibres and protective cover of extruded polymers. Bending Radius: 4 times the internal diameter.

**Surface:** Smooth.

### Identification:

Marked Rylsol Multi.  
Colour: Blue

### Standard length:

100 m rolls up to 12 mm in diameter.  
50 m rolls from 15 mm upwards.

### Temperature Range:

-15°C. to + 60°C.

### Standard:

ISO 1307.

### APPLICATION:

Cleaning of industrial equipment using compressed air (20 bar).

### TECHNICAL DATA

Code	Internal-External Diameter (mm)	Service Pressure (bar)	Bursting Pressure (bar)	Standard Length (m)
02050	6 x 13	20	60	100
02051	8 x 15	20	60	100
02052	10 x 17	20	60	100
02053	12 x 19	20	60	100
02054	15 x 22	20	60	50
02055	19 x 27	20	60	50
02056	25 x 33	20	60	50
02057	30 x 39	20	60	50

### TECHNICAL DATA

Code	Internal-External Diameter (mm)	Weight (g/m)	Roll Weight (kg)	Roll Dimensions (cm)
02050	6 x 13	150	15	40x40x20
02051	8 x 15	180	18	45x45x20
02052	10 x 17	210	21	55x55x20
02053	12 x 19	240	24	58x58x20
02054	15 x 22	270	13	60x60x20
02055	19 x 27	440	22	70x70x20
02056	25 x 33	530	26	80x80x20
02057	30 x 39	610	30	90x90x20